

Hard-wearing material reinforcement



>> Use (\*)

Thanks to its technical characteristics, this glove is suitable for all major works requiring dexterity and a significant protection against mechanical risks including cut (TDM level D). Industrial maintenance, automotive assembly, general handling, making cables, cardboard factory, metal sheet manufacture, aircraft assembly, ...

>> Technical features

- ✓ **Construction:** Seamless knitted liner, long elasticated knitted wrist. HDPE fibers (High Density Polyethylene).
- ✓ **Coating :** Soft polyurethane coating on palm (Open back).
- ✓ **Colour :** grey.
- ✓ **Gauge :** 13.
- ✓ **Sizes :** 7, 8, 9, 10, 11.
- ✓ **Packing :** Carton of 100 pairs. Bundle of 10 pairs.



Learn more : [www.singer.fr](http://www.singer.fr)

>> Main advantages

- ✓ **Seamless knitted liner :** It provides comfort (no roughness or warm-up spots). It increases dexterity for fine object handling.
- ✓ **High-density fibers :** HDPE fibers provides excellent protection against mechanical risks (including the cut).
- ✓ **Protective coating:** The PU coating on palm provides an additional protection to the user and better grip of the handled objects.
- ✓ **Long protection wrist:** For a better protection of the forearm.
- ✓ **Crotch reinforcement between thumb and forefinger :** it reinforces the fragile point of the gloves.

>> Conformity

This glove has been tested according to the following European standards:

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.



It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (**PPE**). **Category II.**

EU type examination certificate (module B) issued by the **CTC**. Notified body n°0075.

Download the EC declaration of conformity on: <http://docs.singer.fr>

EN 388: 2016. Mechanical data (information about levels)	Level 1	Level 2	Level 3	Level 4	Level 5	Levels ▼	EN 388 : 2016  4 X 4 3 D
Abrasion resistance (number of cycles)	100	500	2000	8000	-	4	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	X	
Tear resistance (in Newtons)	10	25	50	75	-	4	
Puncture resistance (in Newtons)	20	60	100	150	-	3	
Cut resistance (N) as per EN ISO 13997	Level A	Level B	Level C	Level D	Level E	Level F	Level ▼
	2	5	10	15	22	30	D

«X means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**

