

UNIQUE NITRILE DUAL LAYER COATING



## &gt;&gt; Use (\*)

Thanks to its technical features, this glove is particularly suitable for all intermediate works requiring a good dexterity. **The unique dual layer coating** allows use in both dry and wet conditions.

Automotive assembly, precision engineering, industrial maintenance, repair of mechanical parts, electronic industry, small parts assembly...

## &gt;&gt; Technical features

- ✓ **Construction:** knitted seamless pattern.  
Elastic knitted wrist. Ventilated back.
- ✓ **Gauge:** 18.
- ✓ **Materials:** - Liner in polyamide.  
- Coating: special double nitrile coating. One first smooth grey coating with an additional black foam coating.  
knuckle coated version.
- ✓ **Colour:** black and grey coating, black liner.
- ✓ **Sizes:** 8, 9, 10.
- ✓ **Packaging:** - Carton of 100 pairs.  
- Bundle of 10 pairs.

Learn more: [www.singer.fr](http://www.singer.fr)

## &gt;&gt; Advantages

- ✓ The gloves are machine knitted liners made from polyamide fibers which gives good fit and sensitivity and superior comfort.
- ✓ The gloves provide good protection in dry and wet handling conditions.
- ✓ Elasticated knitted wrist for a snug fit.
- ✓ The seamless liner provides exceptional comfort and reduces hand fatigue.
- ✓ The unique dual layer coating allows easy use in both dry and wet conditions while keeping good dexterity and flexibility particularly for handling in oily and fatty environments. The soft, foam nitrile outer coating on palm not only enhances protection but it also provides good wet grip by channeling away excess fluid from the surface while the inner nitrile layer provides water repellency.
- ✓ The **ISO 9001** certified manufacturing system guarantees the reliability and consistency of the production.

Light  
handling in  
wet  
environments

## &gt;&gt; Conformity

This glove has been tested according to the following European standards :

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.


It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (module B) issued by **SATRA (Ireland)**. Notified body n°2777

Download the EU declaration of conformity on: <http://docs.singer.fr>



EN 388: 2016. Mechanical data (information about levels)	Level 1	Level 2	Level 3	Level 4	Level 5	Levels ▼	
Abrasion resistance (number of cycles)	100	500	2000	8000	-	4	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	1	
Tear resistance (in Newtons)	10	25	50	75	-	2	
Puncture resistance (in Newtons)	20	60	100	150	-	1	
Cut resistance (N) as per EN ISO 13997	Level A	Level B	Level C	Level D	Level E	Level F	Level ▼
	2	5	10	15	22	30	X



4 1 2 1 X

«X means that the glove has not been submitted to the test.

EN 388 : 2016

EN 388 : 2016



4 1 2 1 X

«X means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**

**SINGER®**  
safety