



HL_PerCap_PERCAP-a

Product Family PerCap Banded Earplugs

Folding banded protection

[Learn more about our products at howardleight.com](http://howardleight.com)

>



Product Numbers & Ordering Information

	Product Numbers	Details
	1030274	PERCAP FOLDABLE BAND CARDED - SNR 24DB Product emphasized in an effective packaging designed for a self-service environment.
	8030274	PERCAP FOLDABLE BAND CARDED - SNR 24DB Product emphasized in an effective packaging designed for a self-service environment.
	1005952	PerCap SNR 24H - 27 M - 20 L - 18
	1005980	PerCap - replacement pods

Overview

Key Features

- Semi-aural protection, super soft pods rest outside the ear canal opening
- Multiple position wear - over the head, under the chin or behind the neck - provides flexibility in wear
- Compact, folding design easy to store in pocket

Recommended Industries/Use

- Wind Energy

Hazards

- Noise

Regulations

- 29 CFR 1910.95 - OSHA Occupational Noise Exposure (US)
- ANSI S3.19-1974 - Attenuation Test Protocol (US)

- Part II, (R.S.C. 1985, c. L-2) - Canada Labour Code
- Z94.2-1994 - Attenuation Test Protocol (CAN)
- 2003/10/EC - EU Hearing Directive
- 89/686/EEC - EU Directive/PPE
- Category II - EC Category/PPE
- EN-13819-2:2002 - EU Standards
- EN 352-2:2002 - EU Standards
- NOHSC: 1007 (2000) - National Standard for Occupational Noise (AUS/NZ)
- NR 15 - Security and Health of Work, Annexes 1 and 2, n°3.214/1978 - Occupational Noise Regulations (BR)
- ANSI S12.6/1997 - Method B - Attenuation Test Protocol (BR)
- 9001:2008 - ISO

Historical Brand

Bilsom

Specifications

Color

- Orange [pod], Black [band]

Pod Shape

- Pod

Material

- Polyurethane Foam [pod], Plastic [band]

Packaging

- Resealable Bag

NRR

- 21

Canada Class

- B(L)

SNR

- 24

SLC*0

- 20 dB / Class 3

EU Certifications

- European Directives – 89/686/EEC
- EC Category PPE – Category II
- Standards – EN-13819-2:2002 / EN-13819-1:2002 / EN 352-2:2002
- EC Certification Number – 961088
- EC Attestation Number – 200422744
- Laboratory – B.G.I.A.

AUS Certifications

- Standardsmark License #1579

Certifications

EU Certificate - Earplugs

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Secured/Hearing_Protection/Earplugs/42685/1033.aspx

EC Declaration of conformity The manufacturer SPERIAN HEARING PROTECTION, LLC, 7828 Waterville Rd. San Diego, CA 92154 United States declares that the Personal Protective Equipment (PPE) items listed below, conform with the provisions of Council Directive 89/686/EEC and, where applicable, with the national standard, tr

Literature & Documents

Instruction Manual - PerCap (global)

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Hearing_Protection/Earplugs/4294986719/1033.aspx

Earplug Instruction Poster - EN

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Hearing_Protection/Earplugs/19799/1033.aspx

Training & Proper Use

1. Position the band under your chin.
2. Use your hands to press the ear pods well into the ear canal using an inward motion.
3. Protection levels are improved by pulling your ear up and back when fitting as shown.
4. In a noisy environment, lightly press the band inward with your fingertips as shown. You should not notice a significant difference in noise level.
5. Proper Fit – If either or both earplugs do not seem to be fitted properly, remove the earplug and reinsert.
6. Removal – Gently twist earplug while slowly pulling in an outward motion for removal.
7. Acoustical Check – In a noisy environment, with earplugs inserted, cup your hands over your ears and release. Earplugs should block enough noise so that covering your ears with your hands should not result in a significant noise difference.

Additional Information

CARE + MAINTENANCE

- INSPECT – Prior to fitting, examine your earpods for dirt, damage or extreme hardness—discard immediately if compromised.
- CLEAN – Wash pods and bands with mild soap and warm water only. Pat dry with a towel. Do not treat with any other substances, as the earpods may degrade and compromise use.
- REPLACE – Replace pods every 2-4 weeks to ensure optimal protection and performance.