Hearing Protection





Technical Details

EAR CUPS AND SPACER: ABS thermoplastic

CUSHION: Polyether & PVC-foil

FOAM LINER: Polyether

BUCKLE AND ARM: POM thermoplastic SLOT ADAPTOR: PA 66 thermoplastic 10% gf

STEEL SPRING: Stainless spring steel

Technology

- Fits most cap-style hard hats on the market with universal slots
- Ear cups can be placed in three positions: usage, stand-by to allow hearing and storage up and away when not needed
- Slim profile design increases stability and reduces risk of snagging in confined spaces
- Smooth telescopic single-point size adjustment increases comfort, stability and wear time
- Soft and wide ear cushions feature snap-in system for easy replacement
- Non-conductive

ORANGE WHP00006

• Certified for use with KASK helmet

The Orange SC3 earmuffs are indicated for use in low frequency noise situations. Suitable for extremely noisy environments such as airports, car racing, while using pneumatic drills, etc.



300 gr SNR >31 dB (A)

SC3 Cap mounted	d, EN 35	52-3:20	02, We	eight 3	00g. P	ZT Gm	bH No	tified E	Body: '	1974		
Frequency Hz	63	125	250	500	1000	2000	4000	8000	Н	М	L	SNR
Mean Attenuation	16,4	17,7	23,5	31,8	41,6	36,4	34,2	35,2				
Std. dev	4,3	3,3	4,2	3,5	3,4	3,8	3,9	5,7	32	29	21	31
APV	12,1	14,4	19,3	28,3	38,2	32,6	30,3	29,5				

Kask combination performance (helmet + earmuffs) - Plasma, HP, Superplasma: SNR 31 - Zenith: SNR 29

SC2

The yellow SC2 earmuffs are suitable for environments with a medium to high level of noise (dB). The best choice in high frequency noise situations. Suitable for a wide variety of uses such as building and construction, forestry use, industrial areas, production areas, agriculture, etc.



271 gr SNR > 26-30 dB (A)

SC2 Cap mounted, EN 352-3:2002, Weight 271g. PZT GmbH Notified Body: 1974												
Frequency Hz	63	125	250	500	1000	2000	4000	8000	Н	М	L	SNR
Mean Attenuation	15,0	15,0	21,0	28,1	35,3	34,0	34,0	37,3				
Std. dev	4,1	2,6	3,1	3,5	4,0	3,8	4,5	4,4	31	27	19	29
APV	10,9	12,4	17,9	24,6	31,3	30,2	29,5	32,9				

Kask combination performance (helmet + earmuffs) - Plasma, HP, Superplasma: SNR 29 - Zenith: SNR 28

SC₁

The green SC1 earmuffs are used in general industrial work areas. Suitable for situations with a low to medium noise level (dB) and with medium to high frequency.



250 gr **SNR** >26 dB (A)

SC1 Cap mounted Frequency Hz	63	125	250	500	1000	2000	4000	8000	Н	М	L	SNR
Mean Attenuation	15,0	15,0	14,7	24,7	33,1	26,8	32,2	34,6				
Std. dev	4,2	3,1	2,9	2,9	3,2	2,7	2,8	3,7	27	23	16	25
APV	10,8	11,9	11,8	21,8	29,9	24,1	29,4	30,9				

Kask combination performance (helmet + earmuffs) - Plasma, HP, Superplasma: SNR 25 - Zenith: SNR 23



YELLOW WHP00005

GREEN WHP00004