



CODICE PRODOTTO: 1032863

**Imbracatura Miller H-Design®
Duraflex™ a 2 punti con 2
anelli e fibbie accoppiate -
Taglia 1.**

Imbracatura Miller H-Design® Duraflex™ a 2 punti con 2 anelli tessili frontali, fibbie accoppiate sul torace e cosciali. Taglia 1

Honeywell
MILLER®**Presentazione generale****Reference Number**

1032863

Tipo di prodotto

Protezione anticaduta

Gamma

Bardatura

Marchio

Miller by Honeywell

Settore

- Building and Construction
- General Industry
- Telecoms
- Utilities

Utilizzo del prodotto

Le imbracature Miller H-Design® rappresentano la nuova generazione di di imbracature per il settore edile e industriale, create per offrire maggiore comfort, libertà di movimento e sicurezza ai lavoratori.

Funzioni e vantaggi**Caratteristiche**

Bretelle: nastro tessile elastico da 44,5 mm Duraflex PES con trattamento PTFE (idrorepellente/antimacchia) Colore: verde con disegno nero Resistenza alla rottura: > 2200 daN

Caratteristiche

Altre cinghie: Nastro nero standard da 44 mm. PES con trattamento PTFE (idrorepellente/antimacchia) Resistenza alla rottura: > 2700 daN

Caratteristiche

Anello a D per ancoraggio dorsale: Materiale: acciaio Finitura: argento zincato Resistenza alla rottura: > 2300 daN

Caratteristiche

Punto di ancoraggio sternale: anelli tessili di dimensioni maggiorate.

Caratteristiche

Fibbie accoppiate in acciaio: Finitura: argento zincato Resistenza alla rottura: > 900 daN

Caratteristiche

Peso: 1,04 kg Resistenza alla rottura: > 15 KN Temperatura: da -30 °C a +50 °C Imbracature complete EN 361

Caratteristiche

Certificata per un carico massimo di 140 kg.

Certificazioni

Categoria DPI

3

Quality Assurance

ISO 9001 / 2000

Attestato EU

Certificato di esame CE 1032862 - 1032863 - 1032864 - 1032865

Certificazioni

- EN 361

Cataloghi & documentazione

1032862-1032863-1032864-1032865 Data Sheet EN

http://www.honeywellsafety.com/supplementary/documents_and_downloads/fall_protection/full_body_harness/4294983956/1033.aspx

Informazioni aggiuntive

User Manual

NT90023600 IND B

Manutenzione

Ciclo di vita

La vita utile prevista dell'imbracatura è di 10 anni a partire dalla data di produzione.

Informazioni per la conservazione

Alcuni fattori possono contribuire a ridurre le prestazioni o la durata del dispositivo

- Stoccaggio scorretto
- Uso scorretto
- Arresto di una caduta
- Deformazione meccanica o taglio
- Contatto con prodotti chimici (acidi o basi)
- Esposizione a fonti di calore estreme > 60 °C
- Esposizione ai raggi UV

Istruzioni per la cura

Attenzione:

- il dispositivo deve essere controllato almeno una volta l'anno da una persona qualificata. L'ispezione deve essere registrata.
- Prima di ciascun utilizzo, il dispositivo deve essere ispezionato visivamente da chi si appresta ad utilizzarlo.

L'ispezione annuale obbligatoria costituirà il fattore decisivo per stabilire se il DPI deve essere utilizzato nuovamente o meno.

Confezione

Codice EAN

63079098

Paese di origine

Francia

© Honeywell International Inc.



by Honeywell

Technical Specifications

Miller H-Design Duraflex™ 2pts Harness w/mating b. & 2 loops

Description:

Miller H-Design Duraflex 2 points harness with 2 webbing loops at the front and mating buckles on chest and legs straps.

The Miller H-Design harnesses are the new generation of harnesses dedicated to construction and general industry sectors providing more comfort, freedom of movements and safety to workers.

Fall indicator on the Front web loops



References:

1032862	H-Design Duraflex 2pts w/mating buckles 2 loops size 0
1032863	H-Design Duraflex 2pts w/ mating buckles 2 loops size 1
1032864	H-Design Duraflex 2pts w/ mating buckles 2 loops size 2
1032865	H-Design Duraflex 2pts w/ mating buckles 2 loops size 3

SIZE SELECTION GUIDE

WEIGHT												
140												
130												
120												
110												
100												
90												
80												
70												
60												
50												
40												
												150

Images are for guidance only.

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com

Benefits:

COMFORT AND FREEDOM OF MOVEMENTS

- Exclusive H architecture of the harness, thanks to its ergonomically placed webbing, providing a total freedom of movements for the arms.
- Horizontal leg straps preventing uncomfortable friction on the legs and on the groin (vs traditional leg straps) increasing comfort for the user during work.
- Stretch webbing on the shoulders to provide even more comfort.

EASY AND QUICK ADJUSTABILITY & CONNECTION

- Easy to access and adjust buckles: intuitive movement up to down.
- Very accessible anchor points: bended position back D-ring
- Adjustable chest strap for a perfect fit in height and width.
- Adjustable leg straps.
- Easy Front strap clip.
- Long front loops for easy connection.



GREATER SAFETY AND EASIER TRACEABILITY:

- Fluo green textile, high visible stitching, front and back fall indicators to facilitate visual inspection before working.



**Fall indicators
on the back plate
for easy inspection**

- Labels improving yearly checking follow-up for a better traceability
- Water-repellent and stain free webbing for greater product durability.
- Hi-visibility vest (option) to see workers even in dark environments (EN ISO 20471)

Features :

Shoulder Straps :

Duraflex Stretch 44,5 mm webbing
PES with PTFE treatment (water repellent / anti stain)
Colour : green with a black drawing
Breaking strength : > 2200 daN

Other Straps :

Standard black webbing 44 mm
PES with PTFE treatment (water repellent / anti stain)
Breaking strength : > 2700 daN

Back Anchorage D-ring :

Material : steel
Finish : Zinc plated Silver
Breaking strength : > 2300 daN

Sternal anchorage point : long webbing loops.

Steel mating buckles :

Finish : Zinc plated Silver
Breaking strength : > 900 daN

Weights

Ref	Designation	Weight (kg)
1032862	H-Design Duraflex 2pts w/ mating buckles 2 loops size 0	1,02
1032863	H-Design Duraflex 2pts w/ mating buckles 2 loops size 1	1,04
1032864	H-Design Duraflex 2pts w/ mating buckles 2 loops size 2	1,06
1032865	H-Design Duraflex 2pts w/ mating buckles 2 loops size 3	1,07

Breaking strength: > 15 KN
Temperature: -30°C to +50°C

EN 361 Full Body Harnesses

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com