

TECHNICAL SHEET



Article: B0643 DARTS
 Norm: UNI EN ISO 20345:2012
 Safety Class: S1 P SRC ESD

ESD Protection: CEI EN 61340-5-1:2008 and CEI EN 61340-4-3:2002

Environmental Class 1 (T=23°C, 12% Relative Humidity)

Footwear height: Mod. A, H 79 mm (< 113 mm, Ref. EN 20345- 5.2.2)

Width 11,

Construction: STROBEL; INJECTED BIDENSITY SOLE

Cleaning and maintenance: Use only soft brushes and water. Do not use substances like alcohol, thinners, gasoline, oil or any other chemicals. Keep the footwear, dry and clean, in a proper place at room temperature.

Suggested fields: Electronic (EPA=Electrostatic protected areas ESD), automotive, automated lines, building, light industry, services

ESD Protection (Electrostatic discharges) for electronic devices

Suitable for use in EPA areas (Electrostatic discharges protected area)

Environmental class 1 (Temperature = 23±2°C; Relative Humidity = 12±3%)



Component	Description	Value	Norm Requirements	Norm
Entire footwear	Total resistance footwear/ground (footwear worn on a metal ground)	1,1 x 10 ⁷ Ω	< 3,5 x 10 ⁷ Ω	CEI EN 61340-5-1
	Sole electrical transversal resistance (footwear resistance)	6,4 x 10 ⁷ Ω	≥ 10 ⁵ Ω e ≤ 10 ⁸ Ω	CEI EN 61340-4-3

Entire footwear: components

Component	Description	Value	Norm Requirements	EN 20345
Metal-free	Impact resistance (200 J)	14 mm		
SLIMCAP toe-cap	Free height after impact		≥ 14 mm	5.3.2.3
	Compression resistance (15 kN) Free height after compression	16 mm	≥ 14 mm	5.3.2.4
Sole (SRC)	Slip resistance	0,38		
	SRA – Sole (entire sole)	0,35	$\geq 0,32$	5.3.5.4
	SRA – Heel (Angle of 7°)	0,18	$\geq 0,28$	5.3.5.4
	SRB – Sole (entire sole)	0,13	$\geq 0,18$	5.3.5.4
	SRB – Heel (Angle of 7°)		$\geq 0,13$	5.3.5.4
Fresh'n Flex (P)	Puncture resistance	No perforation	≥ 1100 N	6.2.1.1.2
Footbed (A)	Antistatic properties			
	Electrical resistance	Dry: $9,19 \times 10^6 \Omega$ Humid: $6,53 \times 10^6 \Omega$	$\geq 10^5 \Omega$, $\leq 10^9 \Omega$ $\geq 10^5 \Omega$, $\leq 10^9 \Omega$	6.2.2.2 6.2.2.2
Sole/Upper	Thermal insulation			
Heat (HI)	Insole temperature increase	N/A	$\leq 22^\circ\text{C}$	6.2.3.1
Cold (CI)	Insole temperature decrease	N/A	$\leq 10^\circ\text{C}$	6.2.3.2
Heel (E)	Shock-absorption in the heel region	31 J	≥ 20 J	6.2.4
(WR)	Water resistance (Water absorption)	N/A	≤ 3 cm ²	6.2.5
(M)	Metatarsal protection	N/A	≥ 40 mm	6.2.6

Upper

Component	Description	Value	Norm Requirements	EN 20345
Suede	Tear resistance	80 N	≥ 60 N	5.4.3
	Traction resistance	N/A	≥ 15 N/mm ²	5.4.4
Microfiber	Water steam permeability	2,8 mg/cm ² h	≥ 0.8 mg/cm ² h	5.4.6
	pH value	N/A	$\geq 3,2$	5.4.7
	Chromium VI	Not detected	Not detectable	5.4.9
	Water passed	N/A	≤ 0.2 g	6.3
	Water absorption	N/A	$\leq 30\%$	6.3

Lining

Component	Description	Value	Norm Requirements	EN 20345
	Tear resistance	30 N	≥ 15 N	5.5.1
	Abrasion resistance	Dry : the surface shows no holes	No holes till 51.200 cycles	5.5.2
3D hi-tech fabric	humid: the surface shows no holes		No holes till 25.600 cycles	5.5.2
	Water steam release	7,8 mg/cm ² h	$\geq 2,0$ mg/cm ² h	5.5.3
	pH value	N/A	Not detectable	5.5.4
	Chromium VI	N/A	Not detectable	5.5.5

Insole				
Component	Description	Value	Norm Requirements	EN 20345
Fresh'n flex	Thickness	3,5 mm	≥ 2,0 mm	5.7.1
	pH value	N/A	Not detectable	5.7.2
	Water absorption	107 mg/cm ²	≥ 70 mg/cm ²	5.7.3
	Water release	98 %	≥ 80 %	5.7.3
	Abrasion resistance (after 400 cycles)	No damage	Damage ≤ to norms reference	5.7.4.1
	Chromium VI	N/A	Not detectable	5.7.5

Removable footbed				
Component	Description	Value	Norm Requirements	EN 20345
Dry'n air	Thickness	3,5±0,5 mm	N/A	5.7.1
	pH value	N/A	Not detectable	5.7.2
	Water absorption	Permeable	Permeable or ≥ 70mg/cm ²	5.7.3
	Water release	Permeable	Permeable or ≥ 80%	5.7.3
	Abrasion resistance	No damage	Dry No holes till 25600 cycles Humid no holes till 12800 cycles	5.7.4.2
	Chromium VI	N/A	Not detectable	5.7.5

Sole				
Component	Description	Value	Norm Requirements	EN 20345
PU Midsole	Sole thickness without profiles	6 mm	≥ 4 mm	5.8.1.1
	Profile height	2,7 mm	≥ 2,5 mm	5.8.1.3
	Tear resistance	5,6 kN/m	≥ 5 kN/m	5.8.2
	Abrasion resistance • relative volume loss	35 mm ³	≤ 250 mm ³	5.8.3
	Flexion resistance • Notches increase after 30.000 cycles	1,5 mm	≤ 4 mm	5.8.4
Outsole TPU SKIN: (TPU high density)	• Hydrolysis	2 mm	≤ 6 mm	5.8.5
	Notches increase after 150.00 cycles	N/A	≥ 4 N/mm; (*) ≥ 3 N/mm with sole ripping	5.8.6
	(HRO) Contact heat resistance (300°C)	N/A	No damage (melting, breaking)	6.4.1
	(FO) Fuel resistance (volume changes)	0,7%	≤ 12%	6.4.2

Date: 08/10/2013

Copy in accordance with the Italian sheet