



TBOB

→ Dielectric overboots



▶ CERTIFICATION

Safety Footwear	EN ISO 20347 I E HRO SRA FO
Electrically Insulating Footwear	EN 50321 Class 0
Dielectric Footwear	ASTM F1117
Personal Protective Equipment	PPE DIR 89/686/EEC

▶ USE

Dielectric boot provides protection of up to 20kV over the complete boot for over three minutes.

▶ TECHNICAL SPECIFICATIONS

Boot Shaft

- Ingenious rear entry design ensures the boot is quick and easy to fit and remove
- Ideal for personnel who have to continually enter and exit hazardous areas
- Yellow dielectric compound shaft
- Seamless construction
- Kick off lug
- REACH Compliant

Boot Sole

- Blue vulcanized rubber sole for maximum grip - 30% better than a conventional safety boot sole
- Slip resistance performance twice that required by EN 13287 SRA and SATRA TM144 standards
- Two to three times the wear resistance of conventional soles
- Fuel and oil resistant
- Greater cut resistance than conventional soles
- Resistance to hot contact 60 seconds 300°C

Care

- Machine washable at up to 40°C
- Shelf life of over 10 years

Sizes

	Medium	Large	Extra-Large
UK	6 - 8	9 - 11	12 - 14
EU	39 - 42	43 - 45	46 - 49
US	7 - 9	10 - 12	13 - 15

Document not contractually binding, errors and omissions excepted.



815B, chemin de Razas - 26780 Malataverne - France
+33 (0)4 75 90 58 00 - www.sf-electric.com

