



Passenger Car Lubricants

Europe Product Catalogue

June 2023



Passenger Car Lubricants

At Gulf, we recognize that each vehicle has unique lubrication requirements and our extensive range of passenger car motor oils addresses these specific needs. Our innovative Gulf Formula and Gulf MAX engine oil ranges exemplify our dedication to providing state-of-the-art technology for modern vehicles.

Gulf Formula



Gulf Formula, featuring advanced ThermoShield Technology, offers superior protection and performance for modern engines under extreme conditions. This fully synthetic oil ensures efficient wear protection and prevents deposit build-up, allowing engines to deliver sustained peak performance.



Gulf MAX



Gulf MAX is designed to enhance engine cleanliness and efficiency. Its unique combination of powerful antioxidants and cleaning agents, paired with high-quality base oils, protects against deposits and sludge build-up, ensuring better performance for longer.

Experience the Gulf difference with our comprehensive selection of passenger car motor oils, designed to provide the perfect lubricant solution for your customers' needs. Trust in Gulf's expertise and innovative technologies to keep your customers on the road, mile after mile.

ENGINE OILS

Gulf Formula LVX 0W-20

Advanced synthetic oil providing enhanced fuel economy, wear protection, and LSPI prevention for various vehicle models.

Specifications: ACEA C5, C6, Ford WSS-M2C947-B1, Ford WSS-M2C962-A1, Opel-Vauxhall 0V0401547, FIAT 9.55535 GSX, Chrysler MS-12145

Approvals: ILSAC GF-6A, API SP (Resource Conserving), API SN-Plus, MB-Approval 229.71 / 229.72, BMW LL-17 FE+, JLR 03.5006

Gulf Formula VFE 0W-20

Ultra-high performance engine oil for Volkswagen vehicles, offering fuel economy, extended drain intervals and Diesel Particulate Filters (DPF) protection.

Specifications: ACEA C5

Approvals: VW 508 00 / 509 00, Porsche C20

Gulf Formula LEF 0W-30

Supreme performance engine oil for modern vehicles, offering fuel economy benefits and compatibility with Diesel Particulate Filters (DPF).

Specifications: ACEA C2, ST JLR.03.5007, FIAT 9.55535-GS1 / 9.55535-DS1

Approvals: Ford WSS-M2C950-A

Gulf Formula PCX 0W-30

Synthetic engine oil for PSA Peugeot Citroën vehicles, offering fuel savings and compatibility with emission reduction systems.

Specifications: ACEA C2, PSA B71 2312

Gulf Formula PCX Plus 5W-30

High-performance engine oil for PSA Peugeot Citroën vehicles, providing fuel savings and DPF/ TWC (Three Way Catalytic Converter) compatibility.

Specifications: ACEA C2, PSA B71 2290

Gulf Formula RNX 5W-30

Synthetic catalyst compatible engine oil that meets low SAPS requirements for most recent models of Renault.

Specifications: ACEA C4, C3, RN 0720, MB 229.51 / 226.51

Gulf Formula CX 5W-30

Advanced mid-SAPS engine oil offering exceptional cleaning power, wear protection and minimized deposits in turbocharged gasoline and diesel engines.

Specifications: ACEA C2, C3, Opel-Vauxhall 040 1547-G30, Opel-Vauxhall 040 1547-D30, MB 229.31

Approvals: API SP, SN Plus, MB-Approval 229.52/ 229.51, BMW Longlife-04

Gulf Formula GVX 5W-30

Synthetic engine oil for Volkswagen vehicles, providing extended drain intervals, deposit control and after-treatment device protection.

Specifications: ACEA C3, API SN, MB 229.31

Approvals: MB-Approval 229.51, Porsche C30, BMW Longlife-04, VW 504 00/ 507 00

Gulf Formula G 5W-30

High-performance synthetic oil for turbocharged gasoline and diesel engines, ensuring long service life and minimized deposits.

Specifications: ACEA A3, B4, RN 0710

Approvals: API SL, MB-Approval 229.3, VW 502 00 / 505 00 , VW 504 00/ 507 00, VW 504 00/ 507 00

Gulf Formula FS 5W-30

Synthetic engine oil designed for Ford vehicles, meeting Euro 4 and 5 emission norms, providing outstanding wear protection and fuel-saving benefits.

Specifications: ACEA A5, B5, FIAT 9.55535-N1

Approvals: Ford WSS-M2C913-D

Gulf Formula GX 5W-40

Cutting-edge synthetic engine oil tailored for high-performance cars and light-duty vehicles, offering superior wear protection and fuel efficiency.

Specifications: ACEA A3, B4, BMW LL-01, RN 0700 / 0710, Porsche A40

Approvals: API SN, MB 229.5, VW 502 00 / 505 00

Gulf Formula ULE 5W-40

Advanced synthetic oil for ultra-low emission engines ensure device protection, prolonged drain intervals and superior performance.

Specifications: ACEA C3, RN 0710 / 0700, Ford WSS-M2C917-A

Approvals: API SN, VW 505 00 / 505 01, MB 229.51/229.31, Porsche A40

Gulf MAX Ultra Plus 10W-40

Semi-synthetic oil for enhanced performance, extended engine life and reduced deposits in turbocharged gasoline and diesel engines.

Specifications: ACEA A3, B4, VW 501 01 / 505 00, MB 226.5, RN 0710 / 0700

Approvals: API SN, MB-Approval 229.3

Gulf MAX 15W-40, 20W-50

High-quality engine oil for turbocharged gasoline and diesel vehicles, ensuring engine cleanliness, wear protection and extended oil life.

Specifications: API CF

Approvals: API SL

Gulf Racing 10W-60

Specialized racing engine oil, delivering optimal performance and reliable protection under high mechanical and thermal loads in motorsport conditions.

Specifications: API SN

Gulf Classic 20W-50

Specially formulated mineral oil for classic gasoline and diesel engines, providing enhanced wear protection and performance.

Specifications: API SF/CF

AUTOMATIC TRANSMISSION FLUIDS

Gulf ATF DX III

High performance fluid for General Motors and Ford automatic transmission vehicles, which exceeds performance requirements of DEXRON®-III G.

Specifications: GM Dexron III G, Ford Mercon

Gulf ATF DX IIIH

Extra high performance fluid for General Motors and Ford automatic transmission vehicles, which exceeds performance requirements of DEXRON® III H.

Specifications: GM Dexron IIIH, Ford Mercon

Approvals: Volvo 97341, ZF TE-ML 04D, 14A, MAN 339 Typ L1 & Z1

Gulf Multi Vehicle ATF

Synthetic fluid for a wide vehicle range that overcomes the limitations of conventional Dexron® III/ MERCON® multi-vehicle formulations.

Specifications: VW G 052 025-A2, VW G 052-162-A1, TL52162; BMW:(AE) LT 71141 – ZF 5 Speed, 7045E (3 Series), ETL-8072B (5 Series), LA2634.

Ford Mercon V. JASO 1-A. MB 236.1 / 236.2 / 236.5 / 236.6 / 236.7 / 236.9, MB 236.10 (NAG-1, MB 5 Speed 1996-2006), MB 236.11 (LT 71141),

MAN 339 V1 / V2 / Z1 / Z2, Volvo 97340 / 97341. Voith H55.6336.XX / US SB 013/118

GEAR OILS

Gulf Gear LS 80W-90

High-performance automotive gear lubricant, developed for limited slip differentials in modern passenger cars and light duty trucks.

Specifications: API GL-5, US MIL-PRF-2105E, API MT-1, Mack GO-J

Gulf Gear MP 80W-90, 85W-140

Superior gear lubricant for excellent protection in a wide range of automotive transmissions, axles and final drives.

Specifications: API GL-5, US MIL-L-2105D

Gulf Syngear 75W-90

Fully synthetic driveline gear lubricant designed for passenger cars and light duty vehicles, providing unmatched protection and performance.

Specifications: API GL-5, MT-1, US MIL-L-PRF-2105E, 2105D, SAE J 2360, Mack GO-J, ZF TE-ML 07A, 08, ArvinMeritor 076-N, DAF, Eaton, Iveco

Approvals: MB-Approval 235.8, MAN 342 Typ S1, MAN 341 Typ Z2, ZF TE-ML 02B, 05A, 12L, 12N, 16F, 17B, 19C, 21A, Scania STO 1:1 G (Gearbox), Scania STO 2:0 A FS

Gulf Syngear FE 75W-80

Synthetic, fuel-efficient gear lubricant for improved fuel economy in passenger cars and light duty vehicles with manual transmissions.

Specifications: API GL-4, Volvo 97307, DAF, Iveco, Renault

Approvals: MAN 341 Typ Z4, ZF TE-ML 01L, 02L, 16K



ANCILLARY FLUIDS

Gulf Antifreeze

British Standard, eco-friendly coolant concentrates for year-round protection, safeguarding engines, cooling systems and seals.

Specifications: BS 6580:1992 and BS 6580: 2010* (*Please refer to product data sheet)

Gulf Antifreeze XLL

Extended Life coolant concentrates with OAT (Organic Acid Technology) for optimal engine protection, high stability, and mixed fleet compatibility.

Specifications: ASTM D3306, ASTM D 4656, AFNOR 15-601, SAE J1034, JASO M325 / JIS K2234, Ford WSS-M97B44-D, Mercedes Benz MB 325.3, General Motors GM 6277M, MAN 324 Type SNF, VW TL 774F

Gulf Brake Fluid DOT4

High-performance poly glycol formula for reliable braking, corrosion protection and compatibility with diverse systems.

Specifications: FMVSS 116 DOT 4

Gulf Coolant 40

British Standard, ready-to-use coolant with MEG, ensuring engine protection, year-round temperature control and eco-friendliness.

Specifications: BS 6580:1992, BS 6580:2010* (*Please refer to product data sheet)

Gulf Coolant XLL

Ready-to-use, extended-life coolant with OAT for enhanced protection, reduced overheating risk, and wide compatibility.

Specifications: ASTM D3306, ASTM D 4656, AFNOR 15-601, SAE J1034, JASO M325/JIS K2234, Ford WSS-M97B44-D, Mercedes Benz MB 325.3, General Motors GM 6277M, MAN 324 Type SNF, VW TL 774F

Gulf Racing Brakefluid DOT 5.1

Supreme performance poly glycol formula designed for racing, offering high boiling points, excellent stability and reliable safety in extreme conditions.

Compatible with ABS and disc brakes.

Specifications: FMVSS 116 DOT 5.1

GREASES

Gulf Crown EP 00, 0, 1, 2, 3

Multipurpose extreme pressure lithium grease for diverse automotive applications, offering excellent wear protection and stability.

Specifications: **NLGI 00:** DIN 51502 KP00K-30, ISO 6743-9 ISO-L-XCCHB00; **NLGI 0:** DIN 51502 KP0K-30, ISO 6743-9 ISO-L-XCCFB0;

NLGI 1: DIN 51502 KP1K-30, ISO 6743-9 ISO-L-XCCFB1; **NLGI 2:** DIN 51502 KP2K-30, ISO 6743-9 ISO-L-XCCFB2; **NLGI 3:** DIN 51502 KP3K-20, ISO 6743-9 ISO-L-XBCFB3

Gulf Crown LC 2

High-performance lithium complex EP grease for wide temperature range use in both automotive and industrial applications.

Specifications: DIN 51502 KP2N-30, ISO 6743-9 ISO-L-XCDIB2

Gulf Crown MP 2.5

Multipurpose lithium grease for heavily loaded automotive applications, providing wear protection, stability and high load carrying capability.

Specifications: DIN 51502 KP2.5K-20, ISO 6743-9 ISO-L-XBCEB2.5

Gulflex EPG 2

High-quality moly grease for industrial and automotive applications, providing wear protection, stability and corrosion resistance.

Specifications: DIN 51502 KPF2K-30, ISO 6743-9 ISO-L-XCCIB2






We go the extra mile to deliver lubricants that keep cars performing at their very best.

Empower your customers to make the choices that help keep their cars on the road for longer.

To find out more, please contact your local Gulf representative.



Scan here to find the right oil for your car.

