



**G-TEK® POLYKOR® X7™
SEAMLESS KNIT POLYKOR® X7™
BLENDED GLOVE WITH NEOFOAM®
COATED PALM & FINGERS
TOUCHSCREEN COMPATIBLE**

- Seamless construction offers increased comfort and breathability
- PolyKor® blended shell with X7™ technology offers high cut resistance and durability with ultra-thin liners
- NeoFoam® coated palm and fingertips offers great abrasion resistance and outstanding wet/dry grip
- Reinforced thumb crotch for extended glove life, enhanced comfort, increased abrasion resistance and added durability in a high-wear area
- Touchscreen compatible to allow the user to operate a touchscreen phone or device without removing gloves
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Washable, resistant to chemicals, water, and ultraviolet light

APPLICATIONS

- Finishing & inspection
- Electronics
- General duty
- Small parts assembly
- Construction
- Maintenance

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

TECHNICAL DATA

| | | | | | |
|-----------------|---|--------------------|---------------------|---------------------|---------------------|
| MATERIAL | PolyKor® with X7™ Technology / NeoFoam® Coating | | | | |
| CONSTRUCTION | Seamless knit | | | | |
| COLOR | Shell: ■ Burgundy/ Coating: ■ Black | | | | |
| WRIST STYLE | Knitted | | | | |
| SIZES | 7- 11 | | | | |
| PACKAGING | 1 pair per bag, 12 pairs per dozen, 72 pairs per case | | | | |
| CASE DIMENSIONS | 15" x 12.2" x 8.7" / 38cm x 31cm x 22cm | | | | |
| CASE WEIGHT | 7 | 8 | 9 | 10 | 11 |
| | 7.5 lbs 3.4 kgs | 8.4 lbs 3.8 kgs | 10.1 lbs 4.6 kgs | 10.4 lbs 4.7 kgs | 10.6 lbs 4.8 kgs |
| COO | China | | | | |

PERFORMANCE PROPERTIES

| | | | | | | |
|---------------------|--|---|---|---|---|---|
| EN388: 4X31C | ASTM F2992-15 ANSI Cut Level A3 (Adopted by ANSI/ISEA 02/16) | | | | | |
| ABRASION | 0 | 1 | 2 | 3 | 4 | - |
| CUT (2003) | X | 1 | 2 | 3 | 4 | 5 |
| TEAR | 0 | 1 | 2 | 3 | 4 | - |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | - |
| CUT (ISO 13997) | A | B | C | D | E | F |



DIMENSIONS (IN/CM)

| | 6 | 7 | 8 | 9 | 10 | 11 |
|----------|-----------|-----------|-----------|------------|-----------|-------------|
| A | 8.3 / 21 | 8.7 / 22 | 9.1 / 23 | 9.6 / 24.5 | 10 / 25.5 | 10.4 / 26.5 |
| B | 2.8 / 7.9 | 3.2 / 8.2 | 3.6 / 9.2 | 3.8 / 9.7 | 3.9 / 10 | 4.1 / 10.3 |
| H | ■ Violet | ■ Red | ■ Yellow | ■ Brown | ■ Black | ■ Blue |

